AMENDMENTS TO THE CLAIMS:

This listing of claims will replace all prior versions, and listings of claims in the application:

LISTING OF CLAIMS:

1. (Original) A method of programming an image acquisition system comprising image reception or detection means, such as a camera, having a field of vision and means of processing the images taken by said camera, in order to define at least one detection area in the field of vision of the camera, characterized in that it consists:
   in placing a sending device (21) in at least one position in the field of vision of the camera and in activating the sending device so that it sends at least one electromagnetic initialization signal or radiation, such as a light signal, having predetermined characteristics, towards the camera when it is in said at least one position,
   in analyzing the content of the images (9a) obtained from the camera so as to recognize said initialization signal, in locating said signal by its coordinates in the images obtained from the camera,
   and in defining, according to a predetermined program, at least one detection area (15) in the field of vision of the camera based on said coordinates of said initialization signal.

2. (Original) The programming method as claimed in claim 1, characterized in that it consists in placing a sending device (21) in turn in at least two positions in the field of vision of the camera and in activating in turn the sending device so that it sends initialization

3

signals having predetermined light characteristics
towards the camera when it is in said positions,
in analyzing the content of the images (9a) obtained from
the camera so as to recognize said initialization
signals,
in locating these signals by their coordinates in the
images obtained from the camera,
and in defining, according to a predetermined program, at
least one detection area (15) in the field of vision of
the camera based on said coordinates of said
initialization signals.

3. (Currently Amended) The programming method as claimed in
    ~~one of claims 1 and 2~~ claim 1, characterized in that it
    consists in prestoring initialization data corresponding
    to said at least one initialization signal, in comparing
    the measured data corresponding to at least one point of
    the images received with this prestored initialization
    data and in determining or computing the coordinates of
    at least one initialization point in the images received
    when the measured data corresponding to this point is
    equal or roughly equal to the stored initialization data.

4. (Currently Amended) The programming method as claimed in
    ~~any one of the preceding claims~~ claim 1, characterized in
    that it consists in defining at least one detection area
    in the field of vision of the camera based on the
    coordinates of at least one received initialization
    signal, the extent and position of which relative to
    these coordinates are predefined.

5. (Currently Amended) The programming method as claimed in
    ~~any one of the preceding claims~~ claim 1, characterized in
    that it consists in defining a detection area in the

4

field of vision of the camera based on the coordinates of
two received initialization signals, located at least on
one side of the line passing through the points
corresponding to these coordinates.

6. (Currently Amended) The programming method as claimed in
~~any one of the preceding claims~~ claim 1, characterized in
that it consists in defining a polygonal detection area
in the field of vision of the camera based on the
coordinates of at least three received initialization
signals, the sides of which pass through the points
corresponding to these coordinates.

7. (Currently Amended) The programming method as claimed in
~~any one of the preceding claims~~ claim 1, characterized in
that said initialization signals have different
predetermined light characteristics.

8. (Currently Amended) The programming method as claimed in
~~any one of the preceding claims~~ claim 1, characterized in
that it consists in analyzing the content of the images
received by digital filtering or thresholding.

9. (Currently Amended) The programming method as claimed in
~~any one of the preceding claims~~ claim 1, characterized in
that each initialization signal is a light signal sent
according to a predetermined modulating frequency and/or
a predetermined chroma.

10. (Original) A device for programming an image acquisition
system comprising image reception or detection means,
such as a camera, having a field of vision and means of
processing the images taken by said camera, characterized
in that it comprises

at least one mobile sending device (21) suitable for sending at least one electromagnetic initialization signal or radiation, such as a light signal, having at least one predetermined characteristic, towards the camera,

and in that the image acquisition system (3) comprises means (13) of recognizing said at least one initialization and location signal to define the coordinates of said at least one initialization signal in the images obtained from this camera

and means (19) for defining, according to a predetermined program, at least one detection area (15) in the field of vision of the camera based on said coordinates of said at least one initialization signal.

11. (Original) The programming device as claimed in claim 10, characterized in that the camera (2) is a video camera and in that said recognition and location means comprise at least one digital filtering or thresholding means (16) in order to compare prestored data with data corresponding to the points of the video signal.

12. (Currently Amended) The programming device as claimed in ~~one of claims 10 and 11~~ claim 10, characterized in that the image acquisition system comprises notification means (46) and means for activating these notification means when the coordinates corresponding to said at least one initialization signal are acquired.

13. (Currently Amended) The programming device as claimed in ~~one of claims 10 and 11~~ claim 10, characterized in that it comprises sending and receiving means (49, 50) associated with the mobile sending device (21) and sending and receiving means (47, 48) associated with said

image acquisition system (3), suitable for exchanging functional signals.

14. (Original) The programming device as claimed in claim 13, characterized in that it comprises synchronization means (53, 54) for synchronizing said mobile sending device (12) and said image acquisition system (13) using synchronization signals exchanged via said sending and receiving means.

15. (Currently Amended) The programming device as claimed in one ~~of claims 13 and 14~~ claim 13, characterized in that it comprises acknowledgement means (51, 52) at least for signaling the end of the definition of said coordinates and/or the end of the definition of said at least one detection area.

16. (Currently Amended) An appliance for the surveillance of at least one predetermined area, characterized in that it comprises a programming device ~~as claimed in any one of claims 10 to 15~~ for programming an image acquisition system comprising image reception or detection means, such as a camera, having a field of vision and means of processing the images taken by said camera, characterized in that it comprises
at least one mobile sending device (21) suitable for sending at least one electromagnetic initialization signal or radiation, such as a light signal, having at least one predetermined characteristic, towards the camera,
and in that the image acquisition system (3) comprises means (13) of recognizing said at least one initialization and location signal to define the

7

coordinates of said at least one initialization signal in the images obtained from this camera
and means (19) for defining, according to a predetermined program, at least one detection area (15) in the field of vision of the camera based on said coordinates of said at least one initialization signal;
wherein the programming device ~~and in that it~~ is programmed according to the method as claimed in ~~any one of claims 1 to 9~~ claim 1.

17. (New) The programming method as claimed in claim 2, characterized in that it consists in prestoring initialization data corresponding to said at least one initialization signal, in comparing the measured data corresponding to at least one point of the images received with this prestored initialization data and in determining or computing the coordinates of at least one initialization point in the images received when the measured data corresponding to this point is equal or roughly equal to the stored initialization data.

18. (New) The programming method as claimed in claim 2, characterized in that it consists in defining at least one detection area in the field of vision of the camera based on the coordinates of at least one received initialization signal, the extent and position of which relative to these coordinates are predefined.

19. (New) The programming method as claimed in claim 3, characterized in that it consists in defining at least one detection area in the field of vision of the camera based on the coordinates of at least one received initialization signal, the extent and position of which relative to these coordinates are predefined.

20. (New) The programming method as claimed in claim 2, characterized in that it consists in defining a detection area in the field of vision of the camera based on the coordinates of two received initialization signals, located at least on one side of the line passing through the points corresponding to these coordinates.